




eCANTER 6S15e


LEFT-HAND DRIVE

MODEL / VEHICLE TYPE		6S15e			
Cab type / crew		Standard, single cab / 3			
Battery variant		S			M
Model variant		84016212	84016312	84016512	84017512
FUSO model code		FEAVKBLCSEU4	FEAVKCLCSEU4	FEAVKELCSEU4	FEAVKELDSEU4
DIMENSIONS [MM]					
Wheelbase		2500	2800	3400	
Overall length		4766	5044	5788	
Cab length		1510			
Width overall		1869			
Cab width		1798			
Height overall		2160		2155	2150
Track width		Front / rear		1390 / 1435	
Frame height (at end of frame)		150			
Ground clearance		260		250	
Cab to rear axle		1975	2279	2879	
Cab to end of frame		3128	3478	4278	
Maximum body length ²⁾		3500	3995	4985	
Frame width		701			
Front overhang		993			
Rear overhang		1145	1195	1395	
Front axle to front of body		625			
Recommended distance cab to body		100			
WEIGHTS [KG]					
Empty weight ¹⁾		2625	2635	2660	3135
Front / rear		1530 / 1095	1555 / 1080	1575 / 1085	1755 / 1380
Gross vehicle weight		6000			
Technical axle loads ¹⁾		2600 / 4500			
Chassis load bearing capacity ²⁾		3375	3365	3340	2865
DRIVING PERFORMANCE AND AGILITY					
Maximum speed		km/h		89	
Minimum turning circle [m]		Kerb to kerb	9,8	10,8	12,8
		Wall to wall	10,8	12,0	14,0

1) The weight refers to the base vehicle (European series, including high voltage battery, tyre sealant, tools and driver with 75 kg) without optional equipment. If any optional equipment is added, the weight changes accordingly.

2) Calculated maximum value which should be checked depending on the body and application.

Subject to change without notice. All data is approximate.



eCANTER 6S15e

LEFT-HAND DRIVE

110 kW (150 hp)
430 Nm

ELECTRIC DRIVE

Type	S40		
Peak output / continuous output	110 kW (150 hp) / 85 kW (116 hp)		
Maximum torque / continuous torque	430 Nm / 250 Nm		
PTO (optional)	Type	mPTO for pump connection	mPTO for pulley
	Maximum torque	222 Nm at 2000 rpm	64 Nm at 7000 rpm
	Continuous power / torque	17 kW / 166 Nm, maximum 2000 rpm	17 kW / 46 Nm, maximum 7000 rpm
	Gear ratio	0.286	–

HIGH VOLTAGE BATTERY

Battery variant	S		M
Capacity usable / installed	kWh	39 / 41	78 / 82
Weight ³⁾	kg	475	950
Range ⁴⁾	km	70	140

CHARGING

Connection type / variants	CCS TYP 2 (AC / DC)		
Maximum charging capacity AC / DC	kW	11 / 70	22 / 104
Maximum charging time AC ⁵⁾	0–100 %	h:min	4:12
Maximum charging time DC ⁵⁾	20–80 %	h:min	0:26
	5–90 %	h:min	0:44

POWERTRAIN

Climbing ability	20 %
------------------	------

CHASSIS

Front axle / rear axle	Independent suspension / E-axle		
Tyres		205/75 R 17.5	
Wheel		17.5 x 6.00 - 115	
Steering	Left-hand drive	Recirculating ball steering with power assist, tilting telescopic steering column with steering-wheel lock	
Brake	Service brake	Hydraulic with vacuum power assist, dual-circuit with load-dependent brake proportioning valve at rear wheels	
	Front / rear	Disc brake (293 x 40 mm / 314 x 35 mm)	
	Parking brake	Electromechanical brake caliper on rear disc brake	
Suspension	Front / rear	Coil springs with shock absorber / Semi-elliptic leaf springs with shock absorber and stabilizer	
Frame	Type	Ladder-type frame with reinforcements and crossmembers	
Electrical system	Low voltage batteries	Series 12 V (80 Ah), optional 24 V (80 + 60 Ah)	

³⁾ The specified weight includes both the battery(ies) with 325 kg each and the peripheral installations (cabling, temperature control, protection, etc.).

⁴⁾ The range depends on various factors such as load, driving style, topography, ambient temperature or weather, battery age, vehicle equipment. The actual range may vary.

The given values for the range were tested with a box body, a load of 50 % of the payload, an ambient temperature of 20 °C and an average battery age.

⁵⁾ The charging time depends on various factors such as the charging capacity of the vehicle and charging station, the battery's state of charge, ambient and battery temperature.

The given values for the charging time were tested under optimum ambient temperature of 20 °C.

The illustrations may contain accessories and items of optional equipment which are not part of the standard specification. The data sheet may contain product types and support services not available in certain countries.